



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/597,974	06/20/2000	Kim B. Roberts	9-13528-104US	9015

20988 7590 02/11/2004
OGILVY RENAULT
1981 MCGILL COLLEGE AVENUE
SUITE 1600
MONTREAL, QC H3A2Y3
CANADA

EXAMINER

HO, THOMAS M

ART UNIT PAPER NUMBER

2134

DATE MAILED: 02/11/2004

4

Please find below and/or attached an Office communication concerning this application or proceeding.

DM

Office Action Summary

Application No.

09/597,974

Applicant(s)

ROBERTS ET AL.

Examiner

Thomas M Ho

Art Unit

2134

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☐ Responsive to communication(s) filed on 20 June 2000.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-59 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-59 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on 20 June 2000 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: _____

DETAILED ACTION

1. Claims 1-59 are pending.

Claim Rejections - 35 USC § 112

2. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claim 48 is rejected under 35 U.S.C. 112, second paragraph, as failing to set forth the subject matter which applicant(s) regard as their invention. Claim 48, c) reads:

“An XOR logic gate adapted to XOR the error count and the received parity value the XOR result being s as the ;”

For the purposes of examination, the Examiner will read claim 48. c) as

“An XOR logic gate adapted to XOR the error count and the received parity value the XOR result being saved as the buffer.”

Claim Rejections - 35 USC § 102

Art Unit: 2134

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

4. Claims 1-15, 19,23, 27-28, 30, 32-33, 35-47, 50, 54, 58 are rejected under 35

U.S.C. 102(e) as being anticipated by Hayward et al.

Tektronix, Inc. discloses in more detail, aspects of the SONET protocol, which are understood to be used by Hayward et al., which is a method and apparatus for routing data packets via a synchronous optical network (SONET).

In reference to claim 1:

Hayward et al. discloses a method of validating a connection mapped between first and second end-nodes via at least one intermediate node in a communications network, the method comprising the steps of:

- a) at the first end-node, inserting performance monitor (PM) information into a predetermined location within the data signal, where the first end node is a packet generating device such as a LAN (Column 4, lines 41 – 44), and the PM information that is inserted is the SONET header information. (Column 4, lines 66 – Column 5, line 5)
- b) at the at least one intermediate node:

- i. extracting the PM information from the predetermined location within the signal received at the intermediate node, where the intermediate node is the transport node. (Column 5, lines 35-39)
 - ii. buffering the extracted PM information. (Column 5, lines 61-62)
 - iii. reinserting the buffered PM information into the predetermined location within the signal prior to, transmitting the data signal toward the second end-node (Column 5, lines 4-5, lines 61-65)
- c) at the second end-node, extracting the PM information from the data signal, where the second end-node is the destination device or output path (Column 5, lines 4-5, lines 61-65)

In reference to claim 2:

Tektronix, Inc. discloses a method wherein the data signal contains a SONET/SDH SPE and the step of inserting the PM information comprises a step of inserting the PM information into a predetermined location within a transport overhead (TOH) outside of the SPE, where the transport overhead is outside of the SPE (Tektronix, page 5, Figure 4 and “**STS-1 SPE in Interior of STS-1 Frames**”), and the PM information(Performance monitoring) is placed in the section overhead. (Tektronix, page 7, “**Section Overhead**”)

In reference to claim 3:

Tektronix, Inc. discloses a method wherein each node in the network is adapted to support a plurality of connection layers and the connection is mapped on one of the plurality of connection

Art Unit: 2134

layers, where the connection layers are the Sections, Lines, and Paths. (Cover Sheet, **“SONET SYSTEM HIERARCHY”**)

In reference to claim 4:

Tektronix, Inc. discloses a method wherein PM information respecting each layer is inserted into a respective predetermined location of the TOH, where the PM information(Performance monitoring) is placed in the section overhead. (Tekronix, page 7, **“Section Overhead”**)

In reference to claim 5:

Tektronix, Inc. discloses a method wherein the step of inserting PM information comprises a step of inserting one or more of a Trace field; a Parity field; and an indicator field, where byte J0 and B1 of the section overhead contains a trace field and a parity field, and bytes H1 and H2 of the line overhead discloses an indicator field. (Tekronix, page 8, **“Table 3. Section Overhead”**, **“Table 4. Line Overhead”**) Bytes J1 and B3 also disclose additional portions of the trace and parity. (Tekronix, page 9, **“Table 5. STS Path Overhead”**)

In reference to claim 6:

Tektronix, Inc. discloses a method wherein the step of inserting a Trace field comprises inserting a nibble of a trace message for communicating information concerning the connection, where inserting the nibble of the trace message comes about with the construction of the STS-1 Frame. (Tekronix, page 8, **“Table 3. Section Overhead”**)

Art Unit: 2134

In reference to claim 7:

Tektronix, Inc. discloses a method wherein the step of inserting the nibble of a trace message comprises a step of inserting successive nibbles of the trace message into respective successive signals until an entire trace message has been sent, where the trace byte J1 is inserted into respective successive signals, in each STS-1 frame. (Tekronix, page 9, **“Table 5. STS Path Overhead”**)

In reference to claim 8:

Tektronix, Inc. discloses a method wherein the step of inserting a Trace field comprises repeating the trace message after the entire trace message has been sent, where the trace message is repeated to verify continued connection to the intended transmitting terminal. (Tekronix, page 9, **“Table 5. STS Path Overhead”**)

In reference to claim 9:

Tektronix, Inc. discloses a method wherein the step of inserting a parity field comprises a step of calculating a parity value in respect of a data signal, and inserting the parity value into a next data signal to be transmitted, where the parity value is calculated and placed in byte B3 (Tekronix, page 9, **“Table 5. STS Path Overhead”**)

In reference to claim 10:

Tektronix, Inc. discloses a method wherein the data signal contains a SONET/SDH SPE and the parity value is a BIP-8, where the BIP-8 is B1. (Tekronix, page 11, **“Table 6. Anomalies,**

Art Unit: 2134

Defects, Failures”)

In reference to claim 11:

Tektronix, Inc. discloses a method wherein the parity value is calculated starting after an H2 byte of a transport overhead (TOH) portion of the signal, and incorporates all SPE bytes until the H2 byte of a next data signal, where the H2 byte is a part of the STS-1 pointer which depicts the offset value to the byte where the SPE begins, this “incorporating” all SPE bytes until the H2 byte of the next signal. (Tekronix, page 12, 3rd paragraph)

In reference to claim 12:

Tektronix, Inc. discloses a method wherein the step of inserting an indicator field comprises a step of accumulating an error count in respect of the data signal, where the indicator field that determines this is the Bit Error Rate. (Tekronix, page 27, Bit Error Rate)

In reference to claim 13:

Tektronix, Inc. discloses a method wherein the data signal is a SONET/SDH signal and the error count is a BIP-8, where each error is determined by BIP-8 (B1). (Tekronix, page 11, “Table 6.

Anomalies, Defects, Failures”)

In reference to claim 14:

Tektronix, Inc. discloses a method wherein the step of extracting the PM information comprises a step of extracting one or more of a trace field, a parity field, and an indicator field, where these

Art Unit: 2134

bytes are extracted by a receiving node, and where byte J0 and B1 of the section overhead contains a trace field and a parity field, and bytes H1 and H2 of the line overhead discloses an indicator field. (Tekronix, page 8, “**Table 3. Section Overhead**”, “**Table 4. Line Overhead**”) Bytes J1 and B3 also disclose additional portions of the trace and parity. (Tekronix, page 9, “**Table 5. STS Path Overhead**”)

In reference to claim 15:

Tektronix, Inc. discloses a method wherein the step of extracting a parity field further comprises a step of calculating a parity value in respect of the received data signal, where the parity field is extracted in order to calculate transmission errors for the previous STS-N frame, already received. (Tekronix, page 8, “**Table 3. Section Overhead**”)

In reference to claim 19:

Tektronix, Inc. discloses a method wherein the step of extracting an indicator field further comprises the steps of:

- a) monitoring the indicator field of each successive received data signal, where the indicator fields are H1 and H2 to determine the starting point of the SPE.
- b) asserting an AIS state if the indicator field of each of first predetermined number of successive data signals contains a first predetermined value, where the indicator bytes H1, and H2 are additionally used to detect STS path Alarm Indication Signals. (AIS-P)

(Tekronix, page 8, “**Table 3. Section Overhead**”)

Art Unit: 2134

In reference to claim 23:

Tektronix, Inc. discloses a method wherein the step of extracting an indicator field further comprises the steps of:

- a) monitoring the indicator field of each successive received signal, where the signals are monitored for an AIS state.
- b) asserting an RDI state if the indicator field of each of a second predetermined number of successive signals contains a second predetermined value, where the RDI state is asserted in the case of an AIS defect.

(Tekronix, page 11, “**Table 6. Anomalies, Defects, Failures**”)

Claim 35 is rejected for the same reason as claim 1.

Claim 36 is rejected for the same reason as claim 2.

Claim 37 is rejected for the same reasons as claim 3.

Claim 38 is rejected for the same reasons as claim 4.

Claim 27, 39 is rejected for the same reasons as claim 5.

Claim 28, 40 is rejected for the same reasons as claim 6.

Claim 41 is rejected for the same reasons as claim 7.

Claim 42 is rejected for the same reasons as claim 8.

Claim 43 is rejected for the same reasons as claim 9.

Claim 44 is rejected for the same reasons as claim 10.

Claim 45 is rejected for the same reasons as claim 11.

Claim 46 is rejected for the same reasons as claim 12.

Claim 47 is rejected for the same reasons as claim 13.

Claim 32 is rejected for the same reasons as claim 14.

Claim 33 is rejected for the same reasons as claim 15.

Claim 30, 50, 58 is rejected for the same reasons as claim 19.

Claim 54 is rejected for the same reasons as claim 23.

5. Claim 1 rejected under 35 U.S.C. 102(e) as being anticipated by Reid et al. , US Patent 6,182,226.

In reference to claim 1:

Reid et al. (Figure 5) discloses a method of validating a connection mapped between first and second end-nodes via at least one intermediate node in a communications network, the method comprising the steps of:

- a. at the first end-node, inserting performance monitor (PM) information into a predetermined location within the data signal, where the PM information is region ID, related the trace attribute of the PM data as defined by the applicant, and the VPN security association.
- b. at the at least one intermediate node, where the intermediate node is the firewall at which the packet is received. (Items 80,82,84,86,88)
 - extracting the PM information from the predetermined location within the

signal received at the intermediate node, where the PM information is extracted by the firewall through decryption and retrieving information from the data fields.

- buffering the extracted PM information, where the information fields collected from the packet are buffered in memory for comparison to meet all the necessary conditions. (Items 92, 94, 96, 98)
- reinserting the buffered PM information into the predetermined location within the signal prior to, transmitting the data signal toward the second end-node, where the data is reinserted and forwarded to the second end node. (Items 98,100)

c. at the second end-node, extracting the PM information from the data signal, where the second end-node must extract the information by decrypting it. (Item 100)

Claim Rejections - 35 USC § 103

6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2134

7. Claims 16-18, 20-22, 24-26, 29, 31, 34, 48-49, 51-53, 55-57, 59 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hayward et al.

In reference to claim 16:

Hayward et al. fails to explicitly disclose a method, further comprising the steps of:

- a) comparing the recalculated parity value with a received parity value contained in the extracted parity field to obtain an error count; and
- b) XORing the error count with the received parity value.

The examiner takes official notice that computing parity values by comparing the calculated parity value against the received parity value is well known to those of ordinary skill in the art. Even bit parity computations would be XORed against an expected value. A value of 1 is returned if a certain bit is flipped. Although it cannot detect where, XORing can detect whether or not a single error has occurred. Examples of this appear in an Error Checking and Correction tutorial, provided by Samsung, and in this Introduction to Error Detection and Correction, by the University of New Brunswick.

It would have been obvious to one of ordinary skill in the art at the time of invention to compare the recalculated parity value with a received parity value and XORing the error count with the received parity value, in order to compute the whether the error count and determine if it was correct.

In reference to claim 18:

Art Unit: 2134

Tektronix, Inc. discloses a method, further comprising a step of accumulating the error count value in respect of the received data signal, where the error count is accumulated in reference to a unit of time. (Tektronix, page 27, Bit Error Rate)

In reference to claim 20:

Hayward et al. fails to explicitly disclose a method, further comprising a step of de-asserting the AIS state if the indicator field of each of the first predetermined number of successive data signals contains a value other than the first predetermined value.

The examiner takes official notice that it is well known to those of ordinary skill in the art to assert an alarm state when a certain condition is met, and to de-assert that when that condition is no longer present.

It would have been obvious to one of ordinary skill in the art at the time of invention to de-assert the AIS state if the indicator field of each of the first predetermined number of successive data signals contains a value other than the first predetermined value, because the signal should not be treated as if it was in an alarm state if in reality, it was not.

In reference to claim 21:

It would have been obvious to one of ordinary skill in the art at the time of invention to set the predetermined number successive data signals to three to achieve a balance between having too few successive states and not knowing whether the AIS should still persist, and having too many successive states and applying actions resulting from the AIS state persisting when it wasn't necessary.

In reference to claim 22:

It would have been obvious to one of ordinary skill in the art at the time of invention to set the first predetermined value is binary "1111", to have a binary state set as cause for the AIS signal. Applicant appears to support this view on (page 7, lines 18- 23) that this number may be "1111" or may be set to a different value.

In reference to claim 26:

Hayward et al. to disclose a method wherein the step of buffering the extracted PM information comprises double-buffering the extracted PM information.

Hayward et al. does disclose buffering the information.

The examiner takes official notice that double buffering was well known to those of ordinary skill in the art at the time of invention with advantages and principles similar to that of buffering.

It would have been obvious to one of ordinary skill in the art at the time of invention to double buffer the extracted PM information to help regulate the differences in transmission speeds in the creation of the packets and allowing access to the PM information when it was needed.

Claim 17, 29, 48 is rejected for the same reasons as claim 16.

Claim 34, 49 is rejected for the same reasons as claim 18.

Claim 51 is rejected for the same reasons as claim 20.

Claim 24, 52 is rejected for the same reasons as claim 21.

Claim 25, 31, 53, 59 is rejected for the same reasons as claim 22.

Claim 55 is rejected for the same reasons as claim 24.

Claim 56 is rejected for the same reasons as claim 25.

Claim 57 is rejected for the same reasons as claim 26.

Conclusion

9. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Thomas M Ho whose telephone number is (703)305-8029. The examiner can normally be reached on M-F from 8:30am – 5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Gregory A. Morse can be reached at (703)308-4789. The fax phone numbers for the organization where this application or proceeding is assigned are (703)746-7239 for regular communications and (703)746-7238 for After Final communications.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703)306-5484.

TMH

February 5th, 2004


GREGORY MORSE
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2100